

**ENVIRO
TAINER™**



RELOCATABLE FUEL STORAGE

**ULC TESTED DUAL WALL FUEL
TANKS FOR YOUR NEEDS**



**HEAVY DUTY ON-DEMAND
CONTAINERIZED FUEL
STORAGE TANKS**

WESTERN®



Western Environmental Canada
petroleum equipment

ENVIROTAINER

ENVIROTAINER XS Specifications



TCS200

27,000 Liter / 7,000 gallon double wall fuel tank. Built in a 20' ISO Hi-Cube container format.
Secondary containment is 110% of inner tank.
Comes as standard with 3" fill, Overfill protection valve. 2" draw off and lockable front cabinet area.



TCS400

60,000 Liter / 16,000 gallon double wall fuel tank. Built in a 40' ISO Hi-Cube container format.
Secondary containment is 110% of inner tank.
Comes as standard with 3" fill, Overfill protection valve. 2" draw off and lockable front cabinet area.

PUMPS AND OPTIONAL FITTINGS. The following options are available:

PUMPS

- Submersible Pumps (208-230 Volt AC) Available in 1/3 HP and 3/4 HP with flow rate up to 50GPM.
- Standard Transfer pumps 12Volt, 24 Volt, 115 or 240 Volt available up to 30 Gallons per minute.
- Engine driven pumps (Gasoline or Diesel driven pumps)

HOSE REELS

- Hand crank
- Spring rewind
- Motor rewind

GAUGES AND OVERFILL ALARMS

- Clock type tank contents gauge
- Float secondary containment monitor
- Electronic Audible and visual alarm (Can be used in either tank of secondary containment).

GENERATOR FEED AND RETURN

- Up to 4 feed and returns from the top of the tank in 1", 3/4" or 1/2"
- Up to 6 feeds from the base of the tank with returns to the top of the tank 1", 3/4" or 1/2"

Other:

- Rear fill point
- Base outlets for pump feed or for connecting multiple tanks
- Spill kits
- Spill containment berms
- Quick release couplings
- Fuel hoses



WESTERN ENVIRONMENTAL CANADA Unit 101-251 Saulteaux Crescent Winnipeg, MB R3J 3C7

P 204 895 0010

TF 866 539 3781

E info@westernenvironmental.ca

F 204 772 6597

W www.westernenvironmental.ca

